Seimi
ÉQUIPEMENTS MARINE



MD45PRHPE

757 Lpm	4 Bar	40m Head	Diesel Yanmar

Diesel

MD45PRHPE

757	4
Lpm	Bar



Pairing the class leading Pacer S Pump with the Yanmar 4.6hp L48V diesel engine gives an ideal combination to perform in any commercial or industrial application. The 2" pump is available with high flow or high pressure impeller with flows up to 871Lpm and pressures up to 4 Bar.



Yanmar L48V Engine

Pump	
Make	Pacer
Model	S Series - SE2UB
Max Flow	757 Lpm
Max Pressure	4 Bar
Body	Corrosion resistant polyester
Seals	Buna (EPDM & Viton available)
Mechanical seal	Carbon ceramic
Impeller	Polyester 706 - 5 vane
Inlet & Outlet	2" NPT female (BSP available)
Suction lift	Up to 7.6m
Notes	Self priming after initial prime

Engine	
Make	Yanmar
Model	L48V
Power	4.6Hp - Gross
Shaft	3/4" parallel keyway shaft
Fuel capacity	2.4 Litres
Lubrication	Oil splash
Oil sensor	Yes
Cooling	Air cooled
Fuel system	Direct injection
Starting	Electric with switch

Weight & Dimensions	
Weight	42.7 Kg
Dimensions	L640 - W445 - H560 mm