Specifications

OctoControl

ARTICLE NUMBER	
60208010	OctoControl Gateway
60208015	OctoControl Basic
60208025	OctoControl Pro
MAIN SPECIFICATIONS	
Input voltage	8 - 32 V
Power consumption	< 100 mA @ 12 V
Operation temperature	- 20 °C to + 40 °C
Storage temperature	-40..80 °C, Relative humidity in operation/ storage up to 95% non-condensing
System communication	WhisperConnect
Weight (kg)	< 0.5
Installation advice	For interior use
OCTOCONTROL GATEWAY SPECIFICATIONS	
60208010	OctoControl Gateway
Dimensions (h x w x d) (mm)	140 x 110 x 42
System support	Up to 3 WhisperPower devices
Cloud integration	Yes
Cloud connection	Builtin 4G
OCTOCONTROL BASIC SPECIFICATIONS	
60208015	OctoControl Basic
Dimensions (h x w x d) (mm)	140 x 170 x 42
System support	Complete WhisperPower systems
MFD integration	Yes
MFD brands supported	Raymarine, Garmin, Simrad, B&G, Furuno
MFD connection	Ethernet
OCTOCONTROL PRO SPECIFICATIONS	
60208025	OctoControl Pro
Dimensions (h x w x d) (mm)	140 x 170 x 42
System support	Complete WhisperPower systems
Cloud integration	Yes
Cloud connection	Builtin 4G **, Ethernet
OctoView support	Yes
OctoView connection	HDMI, USB
MFD integration	Yes

MFD brands supported	Raymarine, Garmin, Simrad, B&G, Furuno
MFD connection	Ethernet