

DURITES ÉCHAPPEMENT

■ Tuyaux d'échappement

- > Homologué Lloyd's
- > Résiste à la chaleur jusqu'à 100° C
- > Pression 3 bars

Réf.	∅ int. (mm)	∅ ext. (mm)	Kg/m	Longueur max (m)	Référence collier de serrage
TE40S	40	48	0,9	20	CTM4751
TE45S	45	53	1,1	20	CTM5155
TE51S	51	60	1,2	20	CTM5963
TE60S	60	69	1,4	20	CTM6873
TE76S	76	85	2	20	CTM8591
TE90S	90	99	2,5	20	CTM97104
TE102S	102	112	3	20	CTM104112
TE125S	125	137	3,7	20	CTM130140
TE150S	150	163	4,2	20	CTM162174
TE203S	203	218	6,9	10	CTM213226
TE254S	254	268	8,5	10	CTM265278
TE305S	305	318	10,9	10	CTM315325



■ Tuyaux d'échappement

- > Homologué Lloyd's

Réf.	∅ int. (mm)	∅ ext. (mm)	Kg/m	Longueur max (m)	Référence collier de serrage
VESLANG40	40	48	0,67	20	CTM4751
VESLANG45	45	53	0,74	20	CTM5155
VESLANG50	51	59	0,83	20	CTM5963
VESLANG60	60	68	0,96	20	CTM6873
VESLANG65	65	73	1	20	CTM6873
VESLANG75	76	84	1,2	20	CTM7985
VESLANG90	90	98	1,6	20	CTM97104
VESLANG100	102	110	2,43	20	CTM104112
VESLANG110	110	120	2,9	20	CTM121130
VESLANG125	127	137	3,3	20	CTM130140
VESLANG150	152	163	5	12	CTM162174
VESLANG203	203	218	8,5	12	CTM213226
VESLANG250	254	270	10	12	CTM265278
VESLANG300	303	323	13	12	CTM317330

