

SNSWITCH control system to be added with the selected WC model.

Sanimarin 41 electric marine toilet - 24 V

Réf : **SN4124V**

Explore comfort and quality with our marine toilets made in France. Featuring a traditional design offering comfortable seating, this equipment is easily installed on the floor with a standard height. Enjoy a quiet, high-performance marine toilet with a low sound pressure level of 46 dB(A). Personalise your experience with our options, including a choice of three control systems.

Classic delivery

Public price TTC
783.58 €

CARACTERISTICS

SANIMARIN 41 ELECTRIC MARINE TOILET - 24 V

Réf. **SN4124V**

Dangerous material : non
Weight :
Catalog page : 237

- Model : Sanimarin 41
- Weight : 26 kg
- Depth : 496 mm
- Height : 411 mm
- Width : 368 mm

SPECIFICATION

Discover marine excellence with Sanimarin 41 toilets, proudly made in France. Traditionally designed, they combine timeless charm with modern functionality. The most comfortable seating guarantees a pleasant experience on board, while the standard height allows easy installation on the floor of your boat.

The Sanimarin 41 toilet offers an unrivalled level of comfort, with an overlapping flap fitted with a drop-brake for safe use. Cutting-edge French engineering is also reflected in the low sound pressure level of 46 dB(A), ensuring peace and quiet while at sea.

To personalise your experience, we offer a choice of three optional control systems. So you can tailor the operation of your marine toilet to your individual preferences.

- Lift parameters: Vertical: 3 m / Horizontal: 30 m
- Integrated non-return valve
- Power consumption: Varies according to the system chosen
- Water consumption: Varies according to the control system chosen, from 1.2 L to 2.4 L
- Water supply :

- On-board fresh water (integrated solenoid valve) or pressurised seawater under pressure
- Minimum dynamic pressure: 1.7 bar
- Recommended flow rate of auxiliary pump: 11 L / min

Control system to be added :

COMFORT electric switch:

- One rinse position
- One grinding/pumping position

The duration of each cycle is controlled by the user, without electronics, and adapts to their needs.

PREMIUM dual button:


- Two automatic cycles: Normal: 2.4 L / Eco: 1.2 L
- Dry bowl control by pressing and holding the large flush button
- Tank full indicator

For ease of installation, this system can be fitted directly to the toilet bowl (except Sanimarin 31).


LUXE control panel:

- Two automatic cycles: Normal: 2.4 L / Eco: 1.2 L
- Dry tank control for emptying in rough seas
- Tank Full indicator for full black water tank

DRAWINGS



FR_Ouvrir le plan



FR_Ouvrir le plan