Centrifugal water pressure system AM60 12V - 0.25 kW - 28 l/min - 2 L tank



Réf : **AM60B12**

AM60-90 bronze hydrophore units with AISI 316 stainless steel shaft. Ideal for pressurising water. Tanks from 2 to 24 L (stainless steel on request). Available in 12V, 24V DC, 230V single-phase, 230/400V three-phase.

Classic delivery

Public price TTC
1,322.66 €

CARACTERISTICS

CENTRIFUGAL WATER PRESSURE SYSTEM AM60 12V - 0.25 KW - 28 L/MIN - 2 L TANK

Réf. **AM60B12**

Dangerous material : non

Weight :

- Capacity : 2 L
- Flow : 28 L/min
- Diameter : 1/2 ""
- Length : 290 mm
- Weight : 8 kg
- Pressure : 2.1 bar
- Power : 0.25 kW
- Height : 250 mm
- Width : 220 mm

SPECIFICATION

AM60-90 hydrophores are designed for demanding applications requiring a reliable, high-performance pressurisation system. Thanks to their robust construction in bronze and AISI 316 stainless steel, they offer excellent corrosion resistance, even in marine or industrial environments.

Technical specifications :

- Bronze pump body, impeller and diffuser for long life and compatibility with fresh and sea water.
- AISI 316 stainless steel shaft for optimum resistance to aggressive environments.
- High-quality mechanical seal for perfect tightness and reduced wear.
- Tanks available in 2, 5, 8 and 24 litres (stainless steel version available on request).
- Motors available in 12V or 24V DC, 230V single-phase, and 230/400V three-phase, offering maximum flexibility according to power requirements.

AM60-90 series hydrophore units are ideal for:

- Water pressurisation on board ships, yachts and pleasure boats.
- Industrial installations requiring a pressurised water supply.

- Supplying drinking or technical water in demanding environments.
- Autonomous water systems with pressurised storage.