EasyFit battery switch 275 A



Réf : **BEP700**

Classic delivery

Public price TTC
78.94 €

CARACTERISTICS

EASYFIT BATTERY SWITCH 275 A

Réf. **BEP700**

Dangerous material : non
Weight : 0,30 kg.

- Dimensions (LxWxH) : 68 x 68 x 110 mm
- Admissible current : 275A
- Maximum current : 455 A
- Length : 2.7 mm
- Weight : 0,7 kg
- Height : 4.3 mm
- Width : 2.7 mm
- Battery switch type : Unipolar

SPECIFICATION

The Easyfit Battery Switch was created for installations where switches need to be recessed through varying thicknesses of panels. It achieves this through an easily removable threaded ring that allows for panel thicknesses up to 3/4"" (19 mm). This switch uses the same features as the 701 with the removable key 45 degree past the off position, labeled handle and a removable back cover covering exposed terminals to meet ABYC specifications. It can also be surface mounted offering a unique style compared to other switches available on the market. BEP Marine Battery Switch Test Procedures (UL 1107) Continuous (1 hour), intermittent (5 minutes) and Cranking (engine starting - 10 seconds). The test is to determine the maximum current the switch can handle for the stated time, without the rear terminals exceeding 100 deg C (212 deg F) above the ambient temperature. The continuous and intermittent ratings are tested at 110 percent of specified ratings. All BEP switches are tested Independently to this specification by a 3rd party laboratory.Can easily be retro-fitted in place of most European post and lever type switchesMolded in high temperature, fiber reinforced plasticsTin-plated copper studs and nutsIgnition-protected