Toxfree XZ1-K electrical cable 1 × 25 mm²

Réf : **CX125**



Halogen-free power cable designed for electrical installations on board ships, offshore platforms and public areas requiring maximum fire safety.

Classic delivery

Public price TTC
11.14 €

CARACTERISTICS

TOXFREE XZ1-K ELECTRICAL CABLE 1 × 25 MM²

Réf. **CX125**

Dangerous material : non

Weight :

- Diameter : 10.9 mm
- External diameter : 10,4 mini/maxi mm
- Weight : 285 kg/km
- Color : Black

SPECIFICATION

In the event of fire, it does not emit toxic or corrosive gases, ensuring the protection of people and equipment.

- Nominal voltage: 0.6/1 kV
- Rigid or flexible electrolytic copper conductor, class 5 (EN/IEC 60228)
- Halogen-free XLPE insulation (HF XLPE) – maximum operating temperature: +90 °C
- Halogen-free polyolefin outer sheath with low smoke emission (type SHF1)
- Flame and fire retardant (IEC 60332-1 & IEC 60332-3-22)
- Low smoke emission and no corrosive gases (IEC 60754 & 61034)
- Operating temperatures: –40 °C to +90 °C (short circuit up to +250 °C / 5 s)
- Excellent mechanical resistance, resistance to oils, UV rays and humidity (AD6)
- Certifications: Bureau Veritas, Lloyd's Register, DNV GL, ABS, CE, RoHS