MPRX marine cable section: 3 x 4 mm²



Réf : **CX34**

Halogen-free power cable designed for electrical installations on board ships, offshore platforms and public areas requiring maximum fire safety.

Classic delivery

Public price TTC
6.23 €

CARACTERISTICS

MPRX MARINE CABLE SECTION: 3 X 4 MM²

Réf. **CX34**

Dangerous material : non
Weight : 0,18 kg.
Catalog page : 283

- Diameter : 10.3 mm
- External diameter : 10.9 mm
- Admissible current : 43 A
- Weight : 195 kg/km
- Bend radius : 50 mm
- Color : Black

SPECIFICATION

In the event of fire, it does not emit toxic or corrosive gases, ensuring the protection of people and equipment.

- Nominal voltage: 0.6/1 kV
- Rigid or flexible electrolytic copper conductor, class 5 (EN/IEC 60228)
- Halogen-free XLPE insulation (HF XLPE) – maximum operating temperature: +90 °C
- Halogen-free polyolefin outer sheath with low smoke emission (type SHF1)
- Flame and fire retardant (IEC 60332-1 & IEC 60332-3-22)
- Low smoke emission and no corrosive gases (IEC 60754 & 61034)
- Operating temperatures: –40 °C to +90 °C (short circuit up to +250 °C / 5 s)
- Excellent mechanical resistance, resistance to oils, UV rays and humidity (AD6)
- Certifications: Bureau Veritas, Lloyd's Register, DNV GL, ABS, CE, RoHS