Hydraulic winch 1500 kg



Réf : **PL5A**

Robust, sealed, and highly efficient hydraulic winch with planetary transmission, providing equal speed for both lifting and lowering (Equal Speed system). Ideal for hoisting and handling applications in demanding environments.

Classic delivery

Public price TTC
N.C.

CARACTERISTICS

HYDRAULIC WINCH 1500 KG
Réf. **PL5A**


Dangerous material : non
Weight : 68,00 kg.
Catalog page : 535

- Capacity : 34 m
- Dimensions : 454 x 284 mm
- Flow : 42 L/min
- Diameter : 9 mm
- Length : 480 mm
- Weight : 68 kg
- Pressure : 141 bar
- Height : 284 mm
- Width : 318 mm
- Drum diameter : 187 mm
- Hauling speed : 18 / 25 m/min
- Pulling force : 22.2 / 16.4 kN
- Cable diameter : 11 mm


SPECIFICATION

- Hydraulic gear motor
- Two-stage planetary transmission
- Automatic multi-disc brake, spring-applied, pressure-released
- Oil-bath lubrication and anti-friction bearings
- Over-running clutch: free rotation when hoisting, locks during lowering for dynamic braking
- Smooth descent control without a counter-balance valve
- Compliant with international safety standards

DRAWINGS



FR_Ouvrir le plan



FR_Ouvrir le plan