CL.0/50 cylinder, torque 292 mkg with hose and by-pass + documentation



Réf : **CL050**

This range of cylinders is designed to be used in difficult applications, as tugboats, trawler, passenger boats etc...

Classic delivery

Public price TTC
3,309.70 €

CARACTERISTICS

CL.0/50 CYLINDER, TORQUE 292 MKG WITH HOSE AND BY-PASS + DOCUMENTATION

Réf. **CL050**

Dangerous material : non
Weight : 33,00 kg.
Catalog page : 40

- Torque : 292 m.kg
- Thread diameter : 1/2 ""
- Rod diameter : 35 mm
- Length : 836 mm
- Weight : 33 kg
- Thrust : 2885 kg
- Pressure : 100 bar
- INITIAL_LETTER_SCHEMA_A : 442 mm
- INITIAL_LETTER_SCHEMA_C : 110 mm
- INITIAL_LETTER_SCHEMA_D : 210 mm
- INITIAL_LETTER_SCHEMA_B : 150 mm
- INITIAL_LETTER_SCHEMA_E : 180 mm
- INITIAL_LETTER_SCHEMA_F : 13 mm
- INITIAL_LETTER_SCHEMA_G : 35 mm
- INITIAL_LETTER_SCHEMA_H : 80 mm
- Tiller arm radius : 138 mm
- Material : steel,Stainless steel

SPECIFICATION

- This series of cylinders is particularly suitable for difficult applications, such as tugs, trawlers, passenger boats, etc.
- Double-acting steel cylinder with stainless steel rod
- Mounted by articulated ball joint
- Supplied with 2 x 0.50 m hose and by-pass