CL.0/150 cylinder torque 1055 mkg

Réf : **CL0150**



This range of cylinders is designed to be used in difficult applications, as tugboats, trawler, passenger boats etc...

Classic delivery

Public price TTC
4,866.05 €

CARACTERISTICS

CL.0/150 CYLINDER TORQUE 1055 MKG

Réf. **CL0150**

Dangerous material : non
Weight : 92,00 kg.
Catalog page : 40

- Torque : 1055 m.kg
- Rod diameter : 50 mm
- Length : 1202 mm
- Weight : 92 kg
- Thrust : 6479 kg
- Pressure : 100 bar
- INITIAL_LETTER_SCHEMA_A : 523 mm
- INITIAL_LETTER_SCHEMA_C : 170 mm
- INITIAL_LETTER_SCHEMA_D : 320 mm
- INITIAL_LETTER_SCHEMA_B : 220 mm
- INITIAL_LETTER_SCHEMA_E : 275 mm
- INITIAL_LETTER_SCHEMA_F : 17 mm
- INITIAL_LETTER_SCHEMA_G : 50 mm
- INITIAL_LETTER_SCHEMA_H : 125 mm
- Tiller arm radius : 220 mm
- Material : steel,Stainless steel

SPECIFICATION

- This series of cylinders is particularly suitable for difficult applications, such as tugs, trawlers, passenger boats, etc.
- Double-acting steel cylinder with stainless steel rod
- Mounted by articulated ball joint
- Supplied with 2 x 0.50 m hose and by-pass