

# Fixed Novec 1230 fire suppression system - auto/manual - 36.8 m³

Réf : **NOV368**

NOVEC extinguishing agent is designed to work instantly by rapidly absorbing heat to stop combustion. Diffusion takes place in less than 10 seconds. NOVEC is non-polluting, safe for humans and the environment, does not significantly reduce oxygen and can be used in occupied spaces. It leaves no residue after diffusion. Activation occurs automatically/manually when the temperature reaches 79°C. We can offer you standard solutions for volumes up to 70 m3 (above that, please consult us).

Classic delivery

**Public price TTC**
**7,120.46 €**

## CARACTERISTICS

**FIXED NOVEC 1230 FIRE SUPPRESSION SYSTEM - AUTO/MANUAL - 36.8 M³**
Réf. **NOV368**

**Dangerous material :** oui
**Weight :** 61,80 kg.
**Catalog page :** 456

- Capacity : 31.8 kg
- Diameter : 254 mm
- Weight : 52 kg
- Height : 841 mm
- For volume up to : 36.8 m³

## SPECIFICATION

NOVEC fixed extinguishing products are designed to protect buildings and equipment from fire. They use a revolutionary inert gas solution, NOVEC 1230, which is safe for people and the environment, yet effective in extinguishing fires quickly. These products are easy to install and maintain, and offer reliable fire protection in a wide range of applications.