Stainless steel 15L ultrasonic tank



Réf : **BNU15**

Ultrasonic cleaning tank. Ultrasonic cleaners are used for impeccable cleaning and degreasing of fragile or complex parts such as carburettors, injectors, etc.

Classic delivery

Public price TTC
694.40 €

CARACTERISTICS

STAINLESS STEEL 15L ULTRASONIC TANK
Réf. **BNU15**

Dangerous material : non
Weight : 10,50 kg.
Catalog page : 149

- Capacity : 15 L
- Dimensions : 330 x 300 x 150 mm
- Weight : 10,5 kg

SPECIFICATION

- 15 L tank and stainless steel housing
- Timer, adjustable thermostat, drain valve
- Supplied with stainless steel basket and lid
- Temperature from 0 to 80°, separate from ultrasonic use
- Analogue version
- Heating power: 400W
- Ultrasonic power: 360W
-

Other additional features :

- 6 Transducers of 40 Khz - 360 Watts effective (540 Watts peak)
- Inner dimensions 33x30x15 cm
- External dimensions 36x33x33 cm
- Mechanical timer from 0 to 30 min with automatic ultrasonic cut-out
- Temperature adjustment from 0 to 80° by electromechanical thermostat
- 400 watt heating power with new technology, reinforced heating plates

- Heating circuit independent of ultrasound (NON-STOP use)
- Drain valve for clean tank emptying
- 10mm stainless steel mesh basket + lid fitted with silicone pads to reduce vibration noise