Cristec HPOWER 12 V 90 A 3 output battery charger



Réf : **HPO1290**

A range of standard, ultra-high-performance HPOWER chargers for professional use in harsh environmental conditions.

Classic delivery

Public price TTC
1,647.44 €

CARACTERISTICS

CRISTEC HPOWER 12 V 90 A 3 OUTPUT BATTERY CHARGER

Réf. **HPO1290**

Dangerous material : non
Weight : 7,96 kg.
Catalog page : 263

- Capacity : 600 - 1200 Ah
- Dimensions : 270 x 360 x 130 mm
- Dimensions (LxDxH) : 270 x 360 x 130 mm
- Nominal current : 90 A
- Charge current : 90 A
- Noise level : < 50 à 1m dB
- Frequency : 45/65 Hz
- Length : 270 mm
- Model : HPO12-90
- Weight : 6,8 kg
- Depth : 130 mm
- Power : 1282 W
- Height : 360 mm
- Type of seal : IP23

SPECIFICATION

Ergonomic design :

- Quick and easy to install: wall-mounting kit supplied
- Robust and lightweight: aluminium casing treated to withstand marine environments
- LED indicators on front panel

Functionality :

- Integrated BUS-CAN interface for data transfer
- Up to 4 chargers connected in parallel to increase charging current

- External sensor for monitoring battery compartment temperature

Number of outputs: 3 separate positive poles, 1 of which is dedicated to the engine battery, BAT E + BAT 1 + BAT2 (integrated splitter). Each output can be used on its own and deliver the total current.