

Raja horizontal windlass version A 2200 W 230-400 V ø 14 mm

Réf : **RJ36AC14SA**

Horizontal windlass available in several versions with 1 or 2 sprockets and/or 1 horizontal or vertical headstock.
Technical study on request.

Classic delivery

Public price TTC
7,071.59 €

CARACTERISTICS

RAJA HORIZONTAL WINDLASS VERSION A 2200 W 230-400 V Ø 14 MM

Réf. **RJ36AC14SA**

Dangerous material : non
Weight : 78,00 kg.
Catalog page : 477

- Weight : 55-70 kg
- Power : 3600 W
- INITIAL_LETTER_SCHEMA_A : 632 mm
- INITIAL_LETTER_SCHEMA_C : 400 mm
- INITIAL_LETTER_SCHEMA_D : 280 mm
- INITIAL_LETTER_SCHEMA_B : 500 mm
- INITIAL_LETTER_SCHEMA_E : 210 mm
- INITIAL_LETTER_SCHEMA_F : 165 mm
- INITIAL_LETTER_SCHEMA_G : 260 mm
- INITIAL_LETTER_SCHEMA_H : 240 mm
- Hauling speed : 12 m/min
- Pulling-out force : 3200 kg
- Continuous pulling force : 700 kg
- Lift force : 700 kg
- Pull-out force : 3200 kg
- Chain diameter : 14 mm
- Drum : with
- Type of windlass : Horizontal

SPECIFICATION

- Version A: 1 sprocket + 1 horizontal headstock
- Version B: 2 sprockets + 1 vertical headstock
- Version C : 1 sprocket + 1 horizontal headstock + 1 vertical headstock
- Other configurations on request