LED robust tri proof 30 W - 3900 lm - 100/305 VAC - IP66



Réf : **RTPL30220**

Lampe à LED robuste tri-proof applicable à une large gamme d'applications intérieures et extérieures telles que les salles des machines, les zones techniques, les ateliers, les magasins, les passages, les ponts, etc. intérieur et extérieur, comme les salles des machines, les zones techniques, les ateliers, les magasins, les passages, les ponts, etc. Disponible avec un circuit d'urgence de 5Watt 20-30Vdc circuit d'urgence de 5Watt 20-30Vdc.

Classic delivery

Public price TTC

379.64 €

CARACTERISTICS

LED ROBUST TRI PROOF 30 W - 3900 LM - 100/305 VAC - IP66

Réf. **RTPL30220**

Dangerous material : non

Weight : 2,70 kg.

Catalog page : 333

- Angle : 230°
- Dimensions : 600 x 105 x 100 mm
- Protection rating : IP66
- Luminous flux : 3900 lm
- Weight : 4 kg
- Power : 30 W
- Color of lighting : White
- Lighting technology : Led

SPECIFICATION

- Aluminium body and stainless steel fixings
- Polycarbonate bowl
- IP67 / -40°C +55°C
- Supplied with 2 cable glands (4 positions)
- Quick connectors without opening
- Adjustable
- 230° wide beam
- Ultra robust (IK10)
- VHF/AIS EMC compatible
- EC models: with emergency lighting