Floodlight FLNG series 300 W - 42000 lm - 100/305 VAC - 30° angle



Réf : **FLNG30023030**

FLNG series LED floodlights for use on terraces and technical applications indoors and outdoors. High power LED panel floodlights with robust design, ideal for mounting on gantries.

Classic delivery

Public price TTC
2,354.05 €

CARACTERISTICS

FLOODLIGHT FLNG SERIES 300 W - 42000 LM - 100/305 VAC - 30° ANGLE

Réf. **FLNG30023030**

Dangerous material : non
Weight : 11,55 kg.
Catalog page : 313

- Angle : 30°
- Dimensions : 345 x 600 x 92 mm
- Protection rating : IP67
- Luminous flux : 48 000 lm
- Weight : 11.6 kg
- Power : 300 W
- Color of lighting : natural white
- Material : stainless steel
- Lighting technology : Led

SPECIFICATION

- Material: Powder coated anodized seawater resistant aluminium
- Finish: White
- Hardware: Marine grade A4 316 stainless steel
- Lens: 90° standard, 30°- and 60° optional
- IP Rating: IP67
- Light Source: 150Watt
- 160Lumens per Watt
- Natural White 3900K
- CRI > 85
- Power Source: Meanwell HLG-185H-C1050B 90-305Vac 50~60Hz
- Dimmable driver (0-10Vdc – PWM – resistance)
- Overload, over-voltage, over-temperature and short
- Potted driver
- Ambient temperature: Operating Temperature -40°C ~ +55°C
- Cable Entry: 1 x M20 Cable Gland Nickel plated brass

- Adjustable A4 316 Stainless Steel bracket
- 0.23 in (6 mm) thickness
- Fixture weight: 18.29 lbs (8,3 kg)