

# Floodlight FLNG series 300 W - 42000 lm - 100/305 VAC - 60° angle

Réf : **FLNG30023060**

FLNG series LED floodlights for use on terraces and technical applications indoors and outdoors. High power LED panel floodlights with robust design, ideal for mounting on gantries.

Classic delivery

**Public price TTC**
**2,014.98 €**

## CARACTERISTICS

### FLOODLIGHT FLNG SERIES 300 W - 42000 LM - 100/305 VAC - 60° ANGLE

Réf. **FLNG30023060**

**Dangerous material :** non
**Weight :** 11,55 kg.
**Catalog page :** 313

- Angle : 60°
- Dimensions : 345 x 600 x 92 mm
- Protection rating : IP67
- Luminous flux : 48 000 lm
- Weight : 11.6 kg
- Power : 300 W
- Color of lighting : natural white
- Material : stainless steel
- Lighting technology : Led

## SPECIFICATION

- Material: Powder coated anodized seawater resistant aluminium
- Finish: White
- Hardware: Marine grade A4 316 stainless steel
- Lens: 90° standard, 30°- and 60° optional
- IP Rating: IP67
- Light Source: 150Watt
- 160Lumens per Watt
- Natural White 3900K
- CRI > 85
- Power Source: Meanwell HLG-185H-C1050B 90-305Vac 50~60Hz
- Dimmable driver (0-10Vdc – PWM – resistance)
- Overload, over-voltage, over-temperature and short
- Potted driver
- Ambient temperature: Operating Temperature -40°C ~ +55°C
- Cable Entry: 1 x M20 Cable Gland Nickel plated brass

- Adjustable A4 316 Stainless Steel bracket
- 0.23 in (6 mm) thickness
- Fixture weight: 18.29 lbs (8,3 kg)