

Piccolo Twin 15 + 15 WhisperPower GRP Sound Shield

Réf : **WP49007080**

By opting for a Twin-Power configuration - using Piccolo gensets in parallel - the end user can double power, while reducing maintenance and fuel costs.

Public price TTC

Classic delivery

N.C.

CARACTERISTICS

PICCOLO TWIN 15 + 15 WHISPERPOWER GRP SOUND SHIELD

Réf. **WP49007080**

Dangerous material : non
Weight : 175,00 kg.
Catalog page : 248

- Bore : 78 mm
- Fuel consumption : 4.2 - 5.6 L/H
- Noise level : 54 dB(A) at 7 m, 65 dB(A) at 1 m dB
- Frequency : 50 Hz
- Length : 882 (each) mm
- Model : Piccolo Twin 15+15
- Motor : Kubota D1105
- Weight : 210 kg
- Max. continuous power : 30 kVA (24 kW)
- Max. intermittent power : 25 kW
- Height : 690 (each) mm
- Width : 570 (each) mm
- RPM : 2200-3600 rpm
- Type of generator : Single-phase

SPECIFICATION

Two identical Piccolo diesel generators operating in parallel. Perfect power solution in case of fluctuations in power demand – for example day and night power consumption. During the day the Twin system operates with 2 running generators, in the evening one generator can be switched off. Save fuel and maintenance costs and reduce emission! Easy to install and configure, just connect the outputs of two generators together! Also a perfect solution in case of height/ weight restrictions. Parallel operation saves at least 25% fuel compared with traditional 1500/1800 Rpm generators.

When two gensets operate in parallel, they also provide a redundant power supply. This means that if one unit fails, the other can take over, ensuring continuity of service. The probability of simultaneous failure of both power supplies is very low, which improves power supply reliability.

Easy to install and configure, simply connect the outputs of two generators together! It's also a perfect solution for weight or height restrictions.