

DC Generator Piccolo GV-3 Kubota WhisperPower - wet exhaust

Réf : **WP49001305**

The advantage of this system is a continuous supply of alternating current. This is achieved through the AC PowerCube inverter of 4, 7, or 14 kVA, which is connected to one or more onboard batteries being charged by one or more DC PowerCubes.

Classic delivery

Public price TTC
18,372.88 €

CARACTERISTICS

DC GENERATOR PICCOLO GV-3 KUBOTA WHISPERPOWER - WET EXHAUST

Réf. **WP49001305**

Dangerous material : non
Weight : 210,00 kg.
Catalog page : 249

- Bore : 67 mm
- Fuel consumption : 2.3 - 3.8 L/H
- Displacement : 719 centimètre cube
- Noise level : 51 dB(A) at 7 m, 60 dB(A) at 1 m dB
- Length : 740
- Model : Piccolo GV 3
- Motor : Kubota D722
- Weight : 175 kg
- Depth : 550 mm
- Power : 8.6 kW
- Max. continuous power : 8.6 kW
- Height : 620 mm
- Width : 740 mm
- RPM : 1500 - 2500 rpm
- Output voltage : 24 V DC,48 V DC

SPECIFICATION

- Number of PowerCube DC units (sold separately) required with the Piccolo GV 3: 2
- Rated output voltage: 24/48 V DC
- Variable-speed diesel engine
- Outstanding noise and vibration control thanks to a revolutionary internal mounting system and highly effective acoustic shields
- Easy installation with external mounting brackets
- WhisperCare compatible
- The PowerCube DC features a universal 90–264 V AC, 45–65 Hz input, enabling shore-powered battery charging regardless of the local power supply
- When combined with a PowerCube AC inverter, the system provides a stable 230 V AC power supply, whether the generator is running

or not

- Complies with Tier 4 EPA and Stage V emissions standards
- Supplied as standard with a DDC remote control panel