

ISO EN12401 certified professional lanyard - RORC-RSO 2018 compliant

Réf : **67494**

So-called single-strap design lanyard: unlike traditional lanyards designed from 2 separate strands, this lanyard is constructed from a single strand along its entire length. This design offers optimal safety and performance.

Classic delivery

Public price TTC
129.11 €

CARACTERISTICS

ISO EN12401 CERTIFIED PROFESSIONAL LANYARD - RORC-RSO 2018 COMPLIANT

Réf. **67494**

Dangerous material : non
Weight :
Catalog page : 445

- Units in box : Mesh bag
- Homologation : ISO 12401 & EC
- Length : Flat lanyard 1 m + extendable lanyard 1.10 to 1.75 m m
- Model : Replica SNSM
- Weight : 570 kg
- Webing width : 25 mm

SPECIFICATION

Fundamentally committed to safety, Plastimo innovates with the SNSM. On each new product development project, Plastimo surrounds itself with experts. To develop this specific lanyard, Plastimo's teams collaborated with the SNSM. The association asked Plastimo to co-develop and manufacture the lanyard that lifeguards will wear on all their operations. This co-development has resulted in a technical and innovative product, now accessible to all boaters.

- Single-strand design: unlike traditional lanyards designed from 2 separate strands, the SNSM-Plastimo lanyard is constructed from a single strand over its entire length. This design offers optimum safety and performance.
- Flexible webbing with retroreflective thread for quick nighttime spotting.
- Double-safety aluminum snap hooks with anti-grip treatment, yellow for attachment to the harness and orange for attachment to the boat. A hard anodizing process optimizes the orange carabiners' resistance to scratching.
- 100 cm short flat strand, 110-175 cm long elastic strand.
- Two overload indicators: when the indicator comes loose, the lanyard needs replacing.
- Delivered with mesh storage pouch.
- Breaking load: 1,650 kg.
- Weight: 570 g.
- Designed in partnership with Les Sauveteurs en Mer.