

Marine Series 65 Base Mounted UV Flame Detector

Réf : **DFL65**

The Series 65 Base Mounted UV Flame Detector is designed to protect enclosed indoor areas where open flaming fires may be expected. Base to be ordered separately.

Classic delivery

Public price TTC
2,278.24 €

CARACTERISTICS

MARINE SERIES 65 BASE MOUNTED UV FLAME DETECTOR

Réf. **DFL65**

Dangerous material : non
Weight : 0,07 kg.
Catalog page : 454

- Homologation : EN54-10 CPR, LPCB

SPECIFICATION

The detector has a single UV sensor with a narrow spectral response in order to discriminate between flames and most spurious sources of radiation.

- Model no. 55000-025APO
- Response type : UV flame detection
- System : Conventional
- Remote indication : Flashing red LED
- Field of view : 90° cone
- Range of view : 0.1m² n-heptane at 25m
- IP rating : IP66
- Supply voltage : 17-28Vdc
- Quiescent current : 550µA
- Cable entry : From rear
- Storage temp. : -40°C to +95°C
- Operating temp. : -40°C to +70°C
- Humidity : 0% to 95% (no condensation or icing)

- Unit weight : 150g
- Dimensions : 100 x 40mm (without base)
- Body material : Polycarbonate
- Unit colour : White