WP Supreme Combi 12V / 2000 - 80A

Réf : **WP61122080**



The WP Supreme Combi will offer you reliable service by providing AC power and 5V USB power for your home, cabin, boat, RV or Trailer using battery power and recharge your battery automatically when utility AC is available.

Classic delivery

Public price TTC
1,596.41 €

CARACTERISTICS

WP SUPREME COMBI 12V / 2000 - 80A
Réf. **WP61122080**

Dangerous material : non
Weight : 6,90 kg.
Catalog page : 268

- Charge current : 80 A
- Frequency : 50 Hz
- Length : 391 mm
- Model : Supreme Combi 12 V / 2000 W - 80 A
- Weight : 8 kg
- Max. continuous power : 2000 W
- Max. intermittent power : 4000 W
- Height : 106 mm
- Width : 302 mm
- Output current : 5.2 A
- Output voltage : 230 V AC

SPECIFICATION

The Sinewave Inverter-Charger can run many AC-powered ap- pliances when you need AC power anywhere. The 5V USB power can charge many USB-powered devices. The multi-stage battery charger will charge different types of batteries.

- Detachable remote on/off display can be mounted anywhere
- Runs small microwave ovens, computers, televisions, powertools and more
- Multistage charger ensures batteries are recharged safety and efficiently
- Sinewave output ideal for running demanding motorloads, sensitive electronics and battery rechargeble devices
- Convert 12V battery power to AC power
- Ideal for boats, trucks and caravans

DISPLAY

- Display Panel Port: RJ12
- Inverter Mode: Input V, Output Power
- Charger Mode: Status, Battery Voltage

BATTERY CHARGER

- AC input voltage 230 VAC - 50Hz
- Charge Voltage Range: 13.5-14.8 V
- Float Voltage Range: 13.4-14.4 V
- Charge current settings: 5, 15, 35, 55, 75, 100
- Charger current (Maximum): 100 ADC
- Charge Control: Bulk / Absorption / Float
- Charging Battery Type: GEL, Flooded, AGM, Lithium, Programmable, Power Supply
- Charger Efficiency: > 80%

AC TRANSFER SWITCH

- Transfer time: < 30 ms
- Transfer Relay: 16 A

SAFETY & ENVIRONMENT

- Conformity marking: CE
- Operating temperature: 0°C to 40°C
- Storage temperature: -20°C to 60°C

POWER SUPPLY

- Available plug sockets: EU - UK - AUS