

LED robust tri proof 30 W - 3900 lm - 100/305 VAC - 50-60 hz - IP66 secours

Réf : **RTPL30220EC**

Robust LED Tri-Proof Light applicable for a wide range of interior- and exterior applications such as engine rooms, technical areas, workshops, stores, passage way, decks, etc. Available with 5Watt 20-30Vdc emergency circuit.

Livraison classique

Prix public TTC
473,53 €

CARACTÉRISTIQUES

LED ROBUST TRI PROOF 30 W - 3900 LM - 100/305 VAC - 50-60 HZ - IP66 SECOURS

Réf. **RTPL30220EC**

Matière dangereuse : non
Poids : 2,70 kg.
Page du catalogue papier : 333

- Angle : 230°
- Dimensions : 600 x 105 x 100 mm
- Flux lumineux : 3900 lm
- Indice de protection : IP66
- Poids : 4 kg
- Puissance : 30 W
- Technologie éclairage : Led
- Tension : 100-305 V AC

SPÉCIFICATIONS

- Aluminium body and stainless steel fixings
- Polycarbonate bowl
- IP67 / -40°C +55°C
- Supplied with 2 cable glands (4 positions)
- Quick connectors without opening
- Adjustable
- 230° wide beam
- Ultra robust (IK10)
- VHF/AIS EMC compatible
- EC models: with emergency lighting